

1st Floor, Above Bhairavnath Post Office,
Opp Pragati Society, Nr. Meera Cross Roads
Maninagar, Ahmedabad - 380028

Tele Fax : + 91-079-25431453, 8140179903

Website :- www.sspumpsindia.com, E-mail :- info@sspumpsindia.com.

POLY-PROPELENE PUMPS "PP" SERIES

FEATURES:-

- Small size bare / monobloc poly propylene pumps.
- Fitted with seal / gland or PTFE bellow Mechanical seal.
- Shaft is of SS-304 / 316 with ceramic coating and (PTFE coating ptional)
- Very economical models as pumps made with minimum parts.
- Very easy maintenance.

APPLICATION:-

Phosphoric acid plants, Gas washing plants, Rayon plants, caustic soda plants for corrosive acids & basics, effluent treatment handling.

PERFORMANCE CHART (WITH SEMI OPEN IMPELLER)

Model	H.P.	Size	Head in Mtr.					Discharge in LPM
			6	8	10	12	16	
PP -2	0.5	25 x 25	0	120	110	90	-	-
PP -3	1	25 x 25	0	150	142	118	60	-
PP -4	1.5	40 x 25	0	162	148	120	90	44

- Performance are at 2900 RPM, 50Hz and tested with clear water.
- Due to constant R & D activity, details are subject to change without prior notice.

Note: Special Pumps for Higher Capacity and Head available on request.

Pp pumps spares

