

1<sup>st</sup> Floor, Above Bhairavnath Post Office,  
Opp Pragati Society, Nr. Meera Cross Roads  
Maninagar, Ahmedabad - 380028

Tele Fax : + 91-079-25431453, 8140179903

Website :- [www.sspumpsindia.com](http://www.sspumpsindia.com), E-mail :- [info@sspumpsindia.com](mailto:info@sspumpsindia.com).

## **MOTORISED BARREL PUMP**

### **PP DIAPHRAGM TYPE BARREL PUMP (AC / DC)**

#### **MODEL: ACAD40 / DCAD40**

MODEL	ACAD40	DCAD40
Pump body material	EPDM	EPDM
Maximum flow rate	40 LPM	40 LPM
Maximum head	15 mtr	15 mtr
Voltage	230 V AC	12 V DC
Self priming	Yes	Yes



### **CI/SS DIAPHRAGM TYPE BARREL PUMP**

<u>PUMP MODEL</u>	<u>MDB CI-1</u>	<u>HDB SS-1</u>
CAPACITY	16 LPM	16 LPM
INLET X OUTLET SIZES	1" X 1"	1" X 1"
WEIGHT		
MATERIAL OF CONSTRUCTION	CAST IRON CONSTRUCTION	SS CONSTRUCTION



## **SS CENTRIFUGAL MOTORISED BARREL PUMP**

### **MODEL MBSS-1**

OUTER DIA :- Ø40 mm,

Power :- 0.88 kw,

Speed :- 10000 RPM, Voltage :- 220v , 50 Hz,

HEAD IN MTRS	0	5	10	15	20	23
CAPACITY IN LPM	43	31	26	16	6.3	SHUT OF
AMPERE	2.8	2.8	2.5	2.5	2.2	2.0



## **PP CENTRIFUGAL MOTORISED BARREL PUMP**

### **MODEL MBPP-1**

OUTER DIA :- Ø40 mm,

Power :- 0.88 kw,

Speed :- 10000 RPM, Voltage :- 220v , 50 Hz,

HEAD IN MTRS	0	5	10	15	20	23
CAPACITY IN LPM	43	31	26	16	6	SHUT OF
AMPERE	2.8	2.5	2.5	2.5	2.2	2.0



## **ALUMINIUM CENTRIFUGAL BARREL PUMP**

### **MODEL MBAL-1**

OUTER DIA :- Ø40 mm,

Power :- 0.88 kw,

Speed :- 10000 RPM, Voltage :- 220v , 50 Hz,

HEAD IN MTRS	0	5	10	12
CAPACITY IN LPM	40	30	15	SHUT OF
AMPERE	2.4	2.3	2.3	2.3



## ROTARY VANE MOTORISED BARREL PUMP

**DC / AC diesel pump Cast iron pump body complete anticorrosive paint**

### DCTP-60



### ACTP-60



Model	Flow rate L/min (max)	Voltage	Current Amp (max)	Duty cycle max	RPM	Connections	Weight kg
DCTP 60 RVB	60	12	18	30 MIN	2800	3/4"	4.2
DCTP 60 RVB	60	24	9	30 MIN	2800	3/4"	4.2
ACTP 60 RVB	80	230	6	<b>CONTINUOUS</b>	280	1"	12 kg

## DC FLAME PROOF BARREL PUMP

### MODEL: DCEX56/ DCEX75



MODEL	<b>DCEX56</b>	<b>DCEX 75</b>
Maximum flow rate	<b>56 LPM</b>	<b>75 LPM</b>
Explosion –Proof motor	<b>¼ HP</b>	<b>¼ HP</b>
Voltage	<b>DC 12 V</b>	<b>DC 12V</b>
Out let size	<b>1"</b>	<b>1"</b>
Threaded tank adapter	<b>2" NPT</b>	<b>2" NPT</b>
Nozzle Hanger	<b>YES</b>	<b>YES</b>