

1st Floor, Above Bhairavnath Post Office,
Opp Pragati Society, Nr. Meera Cross Roads
Maninagar, Ahmedabad - 380028
Tele Fax : + 91-079-25431453, 8140179903

Website :- www.sspumpsindia.com, E-mail :- info@sspumpsindia.com.

FUEL TRANSFER PUMPS

❖ EX PROOF DC POWERED PUMP

MODEL: DCEX56 / DCEX75

This 12 v ex-proof pump is especially for fueling the GASOLINE,(Diesel & Petrol) And its pump head with iron material, and with 100 % copper lining, its specification as follows.

- A : With Ex-proof protection.(CMRI CERTIFICATE IS NOT AVAILABLE)
- B. Pump with by pass and self priming.
- C. Thermal overloads protection.
- D. Filter and connectors
- E. 30 – minute duty cycle / not for continuous operation

MODEL	DCEX56	DCEX 75
Maximum flow rate	56 LPM	75 LPM
Explosion –Proof motor	¼ HP	¼ HP
Voltage	DC 12 V	DC 12V
Out let size	1”	1”
Threaded tank adapter	2” NPT	2” NPT
Nozzle Hanger	YES	YES



MODEL:- ACEX 70

220 V Ex Proof Pump Vane Pump ideal for Diesel & LPG



MODEL	ACEX 70
Voltage	220 v , 50 Hz
Body Material	Cast Iron
Maximum flow meter	70 lpm
Explosion –Proof motor	1/3 hp
Inlet	1”
Outlet	1”
Motor speed	1500

❖ ELECTRIC TRANSFER PUMP (DCTP-40/ 80)

MODEL	DCTP-40	DCTP-80
VOLT	DC12V/24V	DC 12V
POWER	200 WATT	250 WATT
MAXIMUM HEAD	15 MT	15 MT
INLET X OUTLET	¾ “ X ¾ “	1” X 1”
MAXIMUM SUCTION	5 MT	5 MT



❖ **ROTARY VANE PUMP**

ZYB – 50 / ZYB – 80 Vane pump built in air separator, by pass valve, filter is with three different top covers for different connecting pipes. A type, B type and C type. With the advantage of low noise, high flow rate, long life services etc....

MODEL	ZYB-50 / ZYB-80
SPEED	630 RPM
FLOW RATE	45 lpm ~ 65 lpm
VACUUM	> 0.054 MPa
NOISE	<72 db
WORKING PRESSURE	0.16 ~ 0.2 Mpa
NET WEIGHT	17 kg
GROSS WEIGHT	17.5 kg
DIMENSION	340x260 x 370 mm



❖ **BARREL PUMP**

MODEL	FLOW L/MIN	HEAD IN MTRS	POWER KW	SIZE MM	IMPELLER/ OUT LET MATERIAL	PUMP TUBE MATERIAL
MBAL SB-2	110	7 mtr	1.1	50/25	plastic	ALUMINIUM



❖ **AC DIESEL TRANSFER VANE PUMP**

Application:-

- Ideal portable pump for diesel fuel, machine oil.
- As the primary system on earth-moving machinery.
- On mobile fuel pumps on vehicles, such as paving machine, tractor, road roller, etc or in construction yards.

DC / AC diesel pump Cast iron pump body complete anticorrosive paint.



TECHNICAL PARAMETERS:-

Model	Flow rate L/min (max)	Voltage	Current Amp (max)	Duty cycle max	RPM	Connections	Weight kg
ACDT 230V	80	230	6	CONTINUOUS	2800	1"	12 kg

