



TOUGH ENGISOL PVT LTD



1ST First floor , Bhairavnath post office building,
Maninagar,Ahmedabad-380028 India
Tele Fax : + 91-079-25431453,8140179903.

E-mail :- coolantpumps@gmail.com , toughengisol@yahoo.com.

COOLANT PUMPS

“PHULSONS” range of immiscible pumps has been designed especially for filtering systems in the machine tool industry. The low-pressure pumps are available in different flow variants and come with a choice of bottom suction or suction from the top of the volute.

The compact coolant pumps efficiently transport liquid containing chips, fibers and abrasive particles on to the filtering unit. Semi open impellers allow the passing of chips up to 10 mm, making the pumps ideal for removing liquid from any machining process- from boring and milling to grinding.

High – Quality materials :- Carefully chosen materials ensure trouble free operation and long life the top of the pump is made of cast iron, while the impeller is available in composite Bronze/aluminum/engineering plastic etc are used in pumps with flow up to 1000 l/min. in the bigger pumps with higher flow the impellers are made of bronze to ensure perfect Resistance to e.g metal chips. As the pumped liquid will always contain oil there no risk of Corrosion.

Easy Installation:- Easy installation is another of the benefits of the pumps. The tank –mounting flange dimensions’ have been carefully designed to ensure that even replacement of compacting products can be carried out without any inconvenience no special tools are required to the Installation of the coolant pumps just as the entire range is easily serviced and cleaned.

Full – line supplier :- In addition to the range for filtering systems, we offers a wide range of pumps for the cooling and cleaning of tools inside the machine. this allows our customers the benefit of convenient and time –saving one stop shopping.

WIDE RANGE OF APPLICATION

Turning	Grinding	Granite
Boring	Filtration	Fountains
Drilling	Circulation	Washing
Milling	Prininting	Heat treatment
Cutting	Conveyor	Oil Transfer
Sawing	Cooling	

FEATURES:-

- Available in very wide range.
- High **flexibility** of Design.
- Availability in any type of material like CI, SS-316,SS-304,Bronze , Alloy-20 Etc.
- Balanced Shaft & Rotor with excellent grade stamping & wire so highly efficient motor
- Totally Noiseless Operation.
- Available in any length and for any Liquid.
- Extruded powder coated motor body (up to 1 hp)
- No shaft seal (100% Maintenance free 😊.)
- Semi Open Impellers (Ensure free passage of solids and chips)
- Large stock, Earliest Delivery.

TYPE OF COOLANT PUMPS :

- Standard Coolant pumps.
- Coolant pumps with **DC motor**.
- Coolant pumps with **flame proof motor**.
- Coolant pumps with **"C E" and "UL" Mark Motor**
- Custom built coolant pumps for different lengths.
- Very high discharged pump.
- Very high head pump / High pressure pump.
- Pumps in special material like stainless steel, bronze, PP, alloy – 20 etc.
- Multistage Coolant pumps.
- Coolant pump without stem.
- Coolant pump for oil (gear type).
- Submersible Coolant pumps.

COOLANT PUMPS RANGE :

- Max discharge up to **1000 LPM**.
- Max pressure up to **21 bar**.
- Max length up to **1500 mm**.
- Max HP up to **20 HP**.
- Max outlet size **up to 4"**.
- Max temp up to **240° C**.
- Max Size of chips **up to 15 mm**.
- Material or construction – CI / SS Alloy 20 / PP /bronze etc.

SINGLE STAGE HIGH HEAD COOLANT PUMPS (PMS SERIES)

PERFORMANCE CHART OF "PMS" SERIES											
MODEL	OUTLET SIZE	KW/HP	Head in meters VS LPM								
			5	10	15	20	25	30	35	40	45
PMS-100	25 mm	0.37KW /0.5 HP	55	40	15	0	0	0	0	0	0
PMS-120	25 mm	0.75KW/ 1.0 HP	95	70	30	0	0	0	0	0	0
PMS-130	25 mm	1.47 KW/ 1.5 HP	97	85	70	50	15	0	0	0	0
PMS-140	25 mm	1.5 KW/ 2 HP	97	87	80	65	25	10	0	0	0
PMS-150	25 mm	1.8KW/ 2.5 HP	98	90	85	80	65	50	30	0	0
PMS-160	25 mm	2.2 KW/ 3 HP	100	97	95	90	80	70	55	40	10

