

**1st Floor, Above Bhairavnath Post Office,
Opp Pragati Society, Nr. Meera Cross Roads
Maninagar, Ahmedabad - 380028
Tele Fax : + 91-079-25431453, 8140179903**

Website :- www.sspumpsindia.com, E-mail :- info@sspumpsindia.com.

FLOATING PUMP

FLOATING PUMP IN RIVER:-

These special type of pumps have been designed to float in rivers and lakes and sump where level of liquid changing constantly and sometimes liquid required positive suction or low suction. Following are the special features of the pumps.

- Takes both axial and radial loads, specially designed to take thrust loads due to high currents in rivers.
- The centre of gravity is maintained in such a way that the pump will always be in position and even if some heavy logs/animals / external forces in the river try to change its position the pump tends to come to its original floating position when the external lateral force is removed.
- Very easy to maintain: lots of power/energy savings as compared to high suction pumps.
- Pump and floating platform can be made from M.S, PP or SS as per requirement.
- By reason that the floating pump can run in the water , such pumps are helpful for simplifying the earth work and building engineering of pumping station , reducing installation area and saving 30~40% of the total project cost.
- Can solve the flood resistance problem of those rivers and lakes with large fluctuation of water levels.
- Can be supplied up to 200 meter head and 1000 m³/hr
- Floating pumps avoid the need for any civil construction on the river banks.
- Floating pumps are not affected by the fluctuations of the water (tide) levels. Since the pump is always floating, it ensures that the impeller remains submerged. when pump is under water or very low suction head due to floating platform in surface pump.
- Since these pumps are floating , the issue of depth of suction is ruled out.
- Very useful when suction lift is very high.
- Very useful for slurry , hot water and for mining application.



- Always made as per customer's requirement and we use different type of pump and platform as per characteristics of liquid .



